



DOTS SIZE

PIN	1	2	3	4	5	6	7	8	9	10
CONNECTION	VSS	VDD	V0	A0	/CS1	/CS2	NC	NC	R/W	DB0
PIN	11	12	13	14	15	16	17	18	19	20
CONNECTION	DB1	DB2	DB3	DB4	DB5	DB6	DB7	RES	BLA	BLK

Specification:

- 1). Driving: Duty: 1/32, Bias:1/5, VLCD:8.1V(Ref), VDD:5.0V
- 2). Viewing angle: 6 0'clock
- 3). Display mode: STN/Positive/Transflective/YG
- 4). Operating temp.: -20°C~+70°C  
Storage temp.: -30°C~+80°C
- 5). IC: SBN1661(or compatible)
- 6). Backlight: Edge,LED-YG
- 7). Dimensions with mark "\*" are important, with mark "()" are referenced
- 8). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE
A0	First issue	12-29


**深圳市三元晶液晶显示科技有限公司**  
 ShenZhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. SYB12232A3V12-5C13YL3R-B5NGQ  
 模组型号号  
 APPROVED BY \_\_\_\_\_ CHECKED BY \_\_\_\_\_ DRAWING BY \_\_\_\_\_

GENERAL TOL: ±0.3  
 未注公差  
 PAGE: 1 OF 1  
 页码  
 UNIT: mm  
 单位

PROJECTION 三角法  
