



DOTS SIZE
SCALE 5:1

PIN	1	2	3	4	5	6	7	8	9	10
CONNECTION	VDD	VSS	V0	DB0	DB1	DB2	DB3	DB4	DB5	DB6
PIN	11	12	13	14	15	16	17	18	19	20
CONNECTION	DB7	CS1	CS2	/RST	R/W	RS	E	VOUT	BLA	BLK

Specification:

- 1). Driving: Duty:1/64, Bias:1/9, VOUT: -4.9V,V0: -4.6V, VDD:5.0V
- 2). Viewing Direction: 6 O'clock
- 3). Display mode: STN/Positive/Transflective
- 4). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 5). IC: AIP31107andAIP31108
- 6). Backlight: EDGE White
- 7). Dimensions with mark "()" are important, with mark "*" are referenced
- 8). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE
A0	First issue	


深圳市三元晶科技有限公司
 Shenzhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. SYB12864D2 V20 GENERAL TOL: ± 0.3

APPROVED BY CHECKED BY DRAWING BY PAGE? UNIT: mm

Jequill PROJECTION

