



DOT SIZE

**SPECIFICATION:**

- 1). Driving: Duty:1/16, Bias:1/5, Vdd:5.0V, Vlcd:4.5V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Blue
- 4). Operating temp.:0°C~+50°C
- 5). Storage temp.: -10°C~+60°C
- 6). Control IC: SPLC780D1(Or Compatible)
- 7). BACKLIGHT: Edge,White
- 8). DIMENSIONS WITH MARK "\*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	Vo	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REVISION RECORD		REV
First issue		A0



深圳市三元晶液显示科技有限公司  
Shenzhen TCC LCD Hi-Tech Co., Ltd

DRAWING NO.	SYB2004AV12-5C10BL-B5NG	GENERAL TOL:	±0.2
APPROVED BY	CHECKED BY	DRAWING BY	UNIT: mm
		YJQ	PAGE
		2010/9/26	1/1