



INTERFACE:

PIN	SYM.
1	VDD
2	VSS
3	SCK
4	SI
5	LEDA
6	LEDK

逻辑关系表:

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
COM1	1F	1A	2F	2A	3F	3A	4F	4A	10A	10F	9A	9F	8A	8F	7A	7F	6A	6F	5A	5F				COM1
COM2	1G	1B	2G	2B	3G	3B	4G	4B	10B	10G	9B	9G	8B	8G	7B	7G	6B	6G	5B	5G				COM2
COM3	1E	1C	2E	2C	3E	3C	4E	4C	10C	10E	9C	9E	8C	8E	7C	7E	6C	6E	5C	5E				COM3
COM4	T	1D	COL	2D	P1	3D		4D	10D	P2	9D		8D	7D		6D		5D						COM4

SPECIFICATION:

- Driving: DUTY:1/4, BIAS:1/3, VLCD:4.5V, VDD:5.0V
- Viewing angle: 6 O'CLOCK
- Display mode: TBM/Negative/Transmissive
- Operating temp: $-30^{\circ}\text{C}\sim+80^{\circ}\text{C}$
- Storage temp: $-40^{\circ}\text{C}\sim+90^{\circ}\text{C}$
- Controller IC: HT1621
- Backlight: Edge(Orange LED), $V_{LED}=5.0V, I_{LED}=60\text{mA}$
- Dimensions with mark "*" are important, with mark "()" are referenced
- All the raw materials are RoHS complicant

REV	REVISION RECORD	DATE	深圳市三元晶科技有限公司 ShenZhen TCC LCD Hi-Tech Co., Ltd.			
A	Temperature Range	12/08/29	MODEL NO. 模组型号		SYD1035BV10	GENERAL TOL: 未注公差 ± 0.3
B			APPROVED BY 审核		CHECKED BY 检查	DRAWING BY 绘图
C					Luoxian	PAGE: 页面 1 OF 1
D					2012/08/28	UNIT: 单位 mm PROJECTION 三角法



